

## UNCOATED NONWOVEN

### PRODUCT SPECIFICATION \*

Weight DIN EN ISO 536	g/m <sup>2</sup>	152	± 5
Thickness DIN EN ISO 534	µm mil	256 10.1	± 8 ± 0.3
Colour Elrepho UVO (D65) ISO 2469	L a b delta b	97,7 0,1 2,7 3,8	± 0,8 ± 0,5 ± 0,8 ± 0,8
CIE whiteness (D65/10°) min. ISO 2469		> 97	
Opacity min. ISO 2469	%	> 89	

### BENEFITS & PROPERTIES

- Individually developed for digital printing technologies
- Soft-touch feeling
- Homogeneous formation
- Perfect printability
- Perfect handling and edge-to-edge alignment
- Excellent dry strippability
- Perfect smudge and water-resistance
- Flame retardancy B-s1-d0 (according DIN EN 13501-1)
- Free of harmful substances (STANDARD 100 by OEKO-TEX®, Zert.Nr. 17.0.16395)
- Qualified for Xeikon machines (more information: <https://printmedia.xeikon.com/>)
- Certified for HP Latex Inks (more information: <https://www.printos.com/ml/##/medialocator>)

### KEY APPLICATIONS

#### Digital Wallpaper

- Personalised wallpapers
- Photo wallpapers

#### Directions for use

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

\* **Modifications reserved.**

#### Printability

Simplex printable

#### Printing Technology

- Inkjet latex
- Dry toner systems

#### Compatibility

Excellent results on all Dry toner systems as well as on latex and UV printers. Certified for HP Latex Inks. Qualified for Xeikon machines.

#### Certificates



**FLAME  
RETARDANCY**

Flame retardancy



Oeko-Tex



Xeikon

**Certified for  
HP Latex Inks**

Certified for HP Latex Inks