

TEXTILE DIAMOND



MATERIAL DESCRIPTION

Textile Diamond is a 100% polyester perlescent woven fabric with repositionable adhesive. Characterised by the special mother-of-pearl coating and is particularly well-suited for advertising in the beauty, jewellery and fashion sectors or as high-quality textile wall coverings to lend an elegant and exclusive optic. This textile is extremely stable under the effect of heat and may be printed with eco-solvent, solvent, latex and UV inks.

One side printable fabric. PVC-free and certified in accordance with the Oeko-Tex® 100 IV Standard.

PRINTER & INK COMPATIBILITY



PROCESSING INSTRUCTIONS

- **Nature of the to be glued underground:** As smoother the underground as better is the adhesion of Textile Wallcover Diamond to this ground. The undergrounds have to be free of oil, fat, dust, dirt and other impurities and dry.
- **Cleaning of the to be glued surface:** Use non Oil cleaner. Wiper has to be clean, lint-free and non greasy.
- **Pressure:** Strong pressure and good contact between Textile Wallcover Diamond and the to be glued ground is necessary for optimal adhesion. Use a press roller if you install the material with hand. Laminators (e.g.: Rolls Roller) are well suited to stick Textile Wallcover Diamond on exhibition walls, doors or other panels.


PROCESSING AND HANDLING

- The optimal processing is at room temperature between +15 and + 25 °C and humidity of 50-60%. Textile Wallcover Diamond should be stored in the production hall 24 hours before processing.
- Influence of strong heat (e.g.: light, lightspots) can lead to partial peeling off. The to be glued underground (e.g.: wall paper) should have a better adhesion to their base (e.g.: wall) than to Textile Wallcover Diamond.

STORAGE

- Textile Wallcover Diamond should be stored in a sun protected room at a temperature between +15 and +25 °C and a humidity of 50-60% (without direct sun radiation; max. 30 °C).

WEIGHT WITH LINER



FEATURES

- Highest print quality
- Perlescent surface
- Extremely dimensionally stable
- Trimming hot or cold (no fraying)
- Easy handling, print & cut
- Easy to mount

APPLICATIONS

- Wall covering
- Wall tattoo
- Interior design in bars, cafés
- Textile wallpaper

CUTTING

- Cold cutting



The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material.